

# Contech<sup>TM</sup>

SYSTEMS, INC.



WHEN EXPOSED TO AIR<sup>TM</sup>  
**HOT**  
NO HEAT REQUIRED  
SHRINKS

Connector

Protection

Products

PolyChem<sup>TM</sup>

Shrink

PolyFlex SFT-150<sup>TM</sup>

Self-Fusing

Tape



# PolyChem™ Shrink

Flexible EPDM Rubber  
Shrink Tubing for all  
CATV Connections



## Features:

- ▶ Easy installation and re-entry
- ▶ No heat, flame or tools required
- ▶ No craftsmanship required to shrink
- ▶ Eliminates safety hazard with heat or open flame
- ▶ Maximum moisture protection
- ▶ Excellent U.V. and ozone resistance
- ▶ Environmental temperature range -67°F to +302°F  
-55°C to +150°C

## How to Order

### Trunk & Feeder (Hardline)

Example: PCSE-500-P-G-4

Cable Size ..... ↑↑↑↑ ..... Quantity per Pouch  
Connector Type ..... ↑↑↑↑ ..... Connector Manufacturer

Type: P = Pin or Feed Through  
US = Underground Splice  
S = Splice

Manufacturer: G = Gilbert  
L2 = LRC (2 pc.)  
L3 = LRC (3 pc.)  
PP = PPC  
CC = Cablecon

Standard Color: Black

### "F" Connectors

Part Number	Application	Quantity
PCS-RG59/6	"F" Boot RG59 or 6	4, 10, 20
PCS-RG59/6S	"F" Splice RG59 or 6	2, 4, 6
PCS-RG11	"F" Boot RG11	2, 4, 10
PCS-RG11S	"F" Splice RG11	2, 4, 6
PCS-RG7/611	"F" Boot RG7 or 611	2, 4, 10
PCS-RG7/611S	"F" Splice RG7 or 611	2, 4, 6
PCS-CAP-RG59/6	Disconnect Cap RG59/6	4, 10, 20
PCS-CLEAR-RG59/6	Clear I.D. Sleeve	4, 10, 20

Example: PCS-RG59/6-20 (RG59/6 Boot 20 pieces per pouch)

Standard Colors: Black for "F" Boots & Splices, Red for Disconnect Caps  
Other colors, sizes and lengths available.

Total mois  
seal to sav  
during dis  
colors for



Consistent Shrink  
every time without  
heat or flame.

# Typical Physical Properties...

Properties	Value	Test Methods
Tensile Strength	1800 psi	ASTM D-412
Elongation	400%	ASTM D-412
Durometer	60 Shore A	ASTM D-2240
Specific Gravity	1.35	ASTM D-792
Heat Aging	90% Ret.	168 Hrs. @ 136 °C
Water Absorption	<.05%	ASTM D-570
Service Temp. Range	-55°C to +150°C -67°F to +302°F	MS-202C
Dielectric Strength	800 V/MIL	ASTM D-876

The above data represents average test results only.

Should not be used for specification purposes.

Patents applied for.



Maximum moisture  
protection for all  
"F" fittings. Reduces  
costly service calls.



-proof  
nector  
nect. Bright  
tification.



# PolyFlex™ SFT-150

## Self-Fusing Tape

PolyFlexSFT-150 is designed to provide maximum moisture and corrosion protection for all CATV outside plant connections.

SFT-150 is a tough, self-fusing EPR-based tape. It is easy to install and requires no heat or open flame.



It is the perfect product for housing to housing or re-entry protection without interrupting service, as well as providing an excellent jacket repair system.



## Features:

- ▶ Easy Installation and Removal
- ▶ No Heat/Flame Required
- ▶ Excellent Ozone Resistance
- ▶ Superior Low Temp Flexibility -55 F

## How to Order

Part #: PolyFlex SFT-150

Roll Size: 1.5" x 15'

Packaging: 12 Rolls/Case

For  
More  
Information



Customer Service  
CONTECH SYSTEMS, INC.  
P.O. Box 1628  
San Marcos, CA 92079-1628

Tel: (760) 471-1696  
(800) 816-1696  
Fax: (760) 471-2763

E-mail:  
custserv@contechsystems.net